





* In case the operating temperature is out of range, the dashcam will not start and will resume operation after reaching normal operating temperature.



Network data	Global frequency bands		
Micro-SD	0.59" x 0.47" x 0.029" (15 x 12 x 0.76mm)		
GPS	GPS + AGPS		
Road-facing lens	1080p HD 140° wide-angle camera		
In-cabin lens	720p HD with integrated infrared (IR) and adjustable viewing angle		
Auxiliary cameras	Ability to connect up to three auxiliary cameras, wired and Wi-Fi		
Distracted driving events	Cell phone useDriver unbeltedSmoking	Food and drinkDistracted drivingPossible fatigue	
Risky driving events	AccelerationDe-accelerationSharp turnsSpeed limitTamperVibration	 Tailgating G-sensor regular G-sensor high Powered by our accelerometer and g-force metadata 	
Battery for standby mode	The dashcam enters standby mode after the vehicle is turned off. This enables continued streaming and recording from the vehicle.		
AI-12 dimensions	4.5" x 2.3" x 1.9" (115 x 60 x 50mm)		
Weight	5.3oz (150g)		
Casing material	PC2805		
Operating temperature*	Operating: 32°F to 158°F (0°C to 70°C) Storage: 14°F to 185°F (-10°C to 85°C)		
Protective cover	Protective cover over the SIM card and SD card slots, secured with a safety screw		
Power	Hardwire kit is supplied for continuous power. Optional to connect through OBD-II power adapter (12-24V) or IOX cable.		
USB-C port	USB-C port is used for connecting auxiliary camera or for external storage		
Storage/memory	128GB high endurance industrial SD card is supplied with the Al-12. The Al-12 supports up to 512GB.		
Over the air upgrade	Supported		
Speaker	Built-in speaker for audible alerts		
Event trigger button	Built-in button to capture a	Built-in button to capture an unusual event while driving	
Processor	Qualcomm® Snapdragon™ Quadcore Processor		
Warranty	24 month limited	24 month limited	